

Date \_\_\_\_\_

\_\_\_\_\_

Name \_\_\_\_\_

\_\_\_\_\_

Client \_\_\_\_\_

\_\_\_\_\_

Project name \_\_\_\_\_

\_\_\_\_\_

Quote# \_\_\_\_\_

\_\_\_\_\_

Type/Quantity \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_



\_\_\_\_\_

\_\_\_\_\_

25/03/2021 02:58:10

**LOGIC MINI WS**  
**304 31 12**

[Weblink](#)



Cutout shape/size: 55 mm

Recessed depth: 50 mm

Thickness of mounting surface: min.12

Available colors: ALU GREY (304 31 12 A)  
WHITE (304 31 12 W)

1 x LED 0,6W / 3000K / 40lm  
EXCL.LED POWER SUPPLY 24V-DC  
Not Dimmable

LED Technics: Light source: 45 lm // 67 lm/W  
Luminaire: 4 lm // 1 W // 2 lm/W

24V-DC

Class: III

Weight: 0.2 KG

Protection level: IP54

Minimum distance: n.a.

Options: CONCRETE BOX 188

Requirements: LED POWER SUPPLY 24V-DC


For detailed installation instructions, please consult the manual. [304\\_30\\_12\\_HAND.pdf](#)

**LOGIC MINI WS**  
304 31 12

**Related references**

**LED POWER SUPPLIES**

[Weblink / Specsheet](#)



180 36  
63

LED POWER SUPPLY 24V-DC / 150W  
300 89 24 150  
100-240V / 0/50-60Hz  
Number of luminaires: 225

[Weblink / Specsheet](#)




137 16  
50

LED POWER SUPPLY 24V-DC / 24W  
21012 0160  
220-240V / 50-60Hz  
Number of luminaires: 36

**Related references**

**CONCRETE BOXES**

[Weblink / Specsheet](#)



90 90  
10 65  
Ø60

CONCRETE BOX 188  
270 11 188

LOGIC MINI W S  
304 31 12

Related project picture of product family:

