


↓ PRODUCT DESCRIPTION

This unique small precision-articulated spot, part of the Outdoor range, is emblematic of Loupi's expertise. This spot, used for accent outdoor lighting, exploits the advantages of LED technology to the full. less bulk, lower energy consumption and greater efficiency. It is the outdoor version of the Spot C small spot, part of the C range.


↓ OUTPUT




↓ LUMENS




↓ COLOUR RENDERING INDEX



↓ POWER SUPPLY




↓ DIMMING




↓ DEGREES



↓ IP RATING



↓ USE



↓ COLOUR TEMPERATURE



↓ STANDARDS COMPLIANCE



↓ COLOURS



↓ SOURCES

- Luminous flux according to Bining : 200 lumens;
- Colour temperature : 2400 K to 5000 K;
- Service Range : 70 % of nominal flux after 50 000 hours;
- Colour Rendering Index : CRI 80 or CRI 90.

↓ OPTICAL CHARACTERISTICS

- PMMA acrylic lens and window, efficiency ~90 %;
- Honeycomb hexagonal cells 3*3 mm (flow cut at 60°);
- Available degrees : 10°, 18°, 28°, 40° & Elliptic.

↓ ELECTRICAL CHARACTERISTICS

- Constant current supply : 700mA;
- Supply connection : Polarised output connectors;
- Power consumption to 2.1W max, excluding supply;
- Electrical Classification : Class III SELV device.

↓ MECHANICAL CHARACTERISTICS

- Two mounting screws on hook;
- Configurable to aluminum track (series of 3 or 5 spots);
- Operating temperature : -5° +40°;
- ROHS components;
- Exterior use.

↓ SPECIFICITIES

- 3 years guarantee.

↓ NOMENCLATURES

Product Ref.		SC01O			
Specification			AA		
Colour	Black			BK	
	RAL			CU	
Colour temperature	2400K				24
	2700K				27
	3000K				30
	3500K				35
	4000K				40
	5000K				50
Degrees	10°				10
	18°				18
	28°				28
	40°				40
	Elliptique				EL
REFERENCE		SC01O - AA - BK - 30 - 18			